

U.S.S.N.: 09/902,037
Filed: July 10, 2001
Inventors: Peter R. Bloeme et al.

3 a flight plate formed in a central portion of the disc;
4 a transition area joining the annular rim to the flight plate and presenting a sloped
5 surface between the annular rim and the flight plate;
6 a first gripping surface formed of irregular surfaces in at least a first portion of the
7 transition area on an upper side of the disc; and
8 a second gripping surface formed of irregular surfaces in at least a second portion of
9 the transition area on a lower side of the disc;
10 wherein the first and second gripping surfaces provide frictional surfaces to a person
11 throwing the disc

1 4. The disc as set forth in claim 1, wherein the first and second gripping surfaces
2 are comprised of uni-directional surfaces.

1 5. The disc as set forth in claim 1, wherein the first and second gripping surfaces
2 are comprised of segmented, staggered, and uni-directional surfaces.

1 6. The disc as set forth in claim 1, wherein the first and second gripping surfaces
2 have uni-directional surfaces to present a greater frictional force to movement along the disc
3 in a radial direction than to movement along the disc in a tangential direction.

U.S.S.N.: 09/902,037
Filed: July 10, 2001
Inventors: Peter R. Bloome et al.

Sub
C1
A3

10. A disc for being thrown in the air for use with canines, comprising:
an annular rim formed along an outer periphery of the disc and having a diameter less
than 9 inches;
a flight plate formed in a central portion of the disc;
a transition area joining the annular rim to the flight plate and presenting a sloped
surface between the annular rim and the flight plate;
flight plate and transition area having a thickness greater than 0.90 inches;
wherein a ratio of a height of the flight plate to a diameter of the annular rim is less
than 1 to 9.

14. The disc as set forth in claim 11, wherein the first and second gripping surfaces
are comprised of uni-directional surfaces.

A4

15. The disc as set forth in claim 11, wherein the first and second gripping surfaces
are comprised of segmented, staggered, and uni-directional surfaces.

16. The disc as set forth in claim 11, wherein the first and second gripping surfaces
have uni-directional surfaces to present a greater frictional force to movement along the disc
in a radial direction than to movement along the disc in a tangential direction.